

DDSY666 Single Phase DIN-Rail Meter

SWARM series

- STS Standard
- Operating with IHD
- Ultra Anti-Tamper

Chint Global





CHINT GLOBAL PTE. LTD. Building A3, 3655 SiXian Road, Songjiang District, Shanghai, China Tel:+86-21-5677 7777 Web:www.chintglobal.com E-mail:global-sales@chintglobal.com

A CHNT COMPANY

DDSY666 Single Phase DIN-Rail Meter

SPECIFICATIONS

Measurement

- Compliance with STS standard
- Connection type: 1P2W
- Accuracy: Class 1.0 for active

Voltage

- Nominal voltage (Un): 110V, 120V, 220V, 230V, 240V
- Operating range: 0.7Un ~ 1.2Un
- Power consumption: ≤ 1.5 W, 5VA

Current

• 5(60)A/5(80)A/5(100)A

Frequency

• 50Hz or 60Hz

Real-time Clock

• Accuracy within 0.5 seconds per day at 23° C

LCD Display

- Number of flashes per kWh
- Communication indication
- Relay indication

Battery (Optional)


- Built-in Battery
- Voltage: 3.6V nominal
- Backup time: 15 years with power

Measured Values


- Total kWh
- Instantaneous kW, Irms, Vrms
- Cumulative and credit energy

METER DIMENSIONS





103







Zhejiang CHINT Instrument & Meter Co., Ltd

Add: No.560, Yueming Road, Binjiang District, Hangzhou, Zhejiang, China P.C: 310052 Tel: +86-571-56977777 Fax: +86-577-62919588 E-mail: chintmeter@chint.com Website:http://en.chintim.com/

Relay

- One relay
- Up to 10000 operations

Communications

- Optical port
- PLC/M-Bus (optional) communication with IHD
- Protocol: IEC62056-21
- Communication with DCU through PLC (optional)

Event Logs (Optional)

- Standard event, tamper event, control event, grid event
- Configurable event alarming system (LED and buzzer)
- Meter tamper state indication on IHD LCD and LED

Security

- Compatibility STS
- 20 digits token transfer

Environmental

- Operating range limit: -40° C to +75° C
- Storage range limit: -40° C to +85° C
- Relative humidity: \leq 95%RH
- Ingress protection: IP54

Dimensions and Weight

- Dimensions: 143mm ×103mm × 55.4mm
- Weight: 0.6 kg (Approx.)