

# ATTESTATION OF CONFORMITY

Issued to: Zhejiang Chint Electrics Co., Ltd.  
No.1, Chint Road, Chint Industrial Zone, North Baixiang, Yueqing, 325603 Zhejiang, China

For the product: Moulded-case circuit-breaker

Trade name: CHINT

Type/Model: NM8NDC-125B, NM8NDC-125C, NM8NDC-125S, NM8NDC-125Q, NM8NDC-125H

Ratings: Ue: 1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P, 250 Vdc for 1P  
In: 16 A, 20 A, 25 A, 32 A, 40 A, 50 A, 63 A, 80 A, 100 A, 125 A  
See annex for further ratings

Manufactured by: Zhejiang Chint Electrics Co., Ltd.  
No.1, Chint Road, Chint Industrial Zone, North Baixiang, Yueqing, 325603 Zhejiang, China

Requirements: BS EN 60947-2:2017+A1:2020, BS EN 60947-5-1:2017

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential test reports no. 3321421.50 issued on 2022-03-25, 3321421.51 issued on 2022-03-25, CQC CB test report no. 00901-CB2018CQC-084130 issued on 2019-03-25 with CB test certificate no. CN46412 issued on 2019-04-09 and CQC CB test report no. 00901-CB2018CQC-084130-M1 issued on 2019-06-06 with CB test certificate no. CN46412-M1 issued on 2019-06-18.

This Attestation implies that the examined types are in accordance with the standards designated under the Electrical Equipment (Safety) Regulations 2016.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The UKCA marking may be affixed on the product if all relevant and effective UK regulations are complied with.

Wenzhou, Zhejiang, 2 April 2022

Number: 3321421.02A

DEKRA Testing Services (Zhejiang) Co., Ltd

Ms J Guo  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

DEKRA Testing Services (Zhejiang) Co., Ltd

No. 5. Changjiang Road, Great Bridge Industrial Park, North Baixiang, Wenzhou, 325603 Zhejiang, ZJ, China  
T +86 57762 868000 F +86 57762 919889 www.dekra-product-safety.com

UK  
CA

# Annex

Document no.	: Attestation Number 3321421.02A
<b>Ratings</b>	
Rated insulation voltage (Ui)	: 1000 V for main circuit 500 V for shunt release and under-voltage release (2P, 3P and 4P) 500 V for electric operating mechanism (3P and 4P) 500 V for auxiliary circuit (2P, 3P and 4P)
Rated impulse withstand voltage (Uimp)	: 8 kV for main circuit 2,5 kV for shunt release and under-voltage release (2P, 3P and 4P) 6 kV for electric operating mechanism (3P and 4P) 2,5 kV for auxiliary circuit (2P, 3P and 4P)
Rated current (In)	: 16 A, 20 A, 25 A, 32 A, 40 A, 50 A, 63 A, 80 A, 100 A, 125 A
Conventional thermal current (Ith)	: Equal to In
Suitable for photovoltaic (PV) systems	: Suitable
Suitable for isolation	: Suitable
Selectivity category	: A
Safety distance (screen-circuit breaker)	: Front / back: 0 mm Left / right: 0 mm Up / down: 0 mm
Reference temperature	: 40 °C
Method of mounting	: Fixed
EMC Environment	: A
Tightening torque for terminals	: 6,0 Nm for M6
Line/load terminal	: Immaterial
Connection	: copper conductor with cable lug
Inverse time delay release	: Ir (inverse time delay tripping setting): For thermal magnetic type for 2P, 3P and 4P: Ir: (0,7 / 0,8 / 0,9 / 1,0) x In For thermal magnetic type for 1P: Ir: 1,0 x In
Time setting of the inverse time delay release	: Fixed, trip time at 2 In: 60 s ≤ t ≤ 600 s
Instantaneous release	: Ii (instantaneous tripping setting): Ii: 10 In
Shunt release	: SHT21-M8 for 2P, 3P and 4P: AC: 48 V, 110 V, 220 - 240 V, 380 - 415 V, 50 / 60 Hz DC: 24 V, 48 V, 110 - 120 V, 220 V
Under-voltage release	: UVT21-M8 for 2P, 3P and 4P: AC: 48 V, 110 V, 220 - 240 V, 380 - 415 V, 50 / 60 Hz DC: 24 V, 48 V, 110 - 120 V, 220 V
Electric operating mechanism	: MOD21-M8 for 3P and 4P: AC: 110 V, 220 - 240 V, 380 - 415 V, 50 / 60 Hz DC: 24 V, 110 V, 220 V



Auxiliary circuits : AX21-M8 / AL21-M8 for 2P, 3P and 4P:  
 1 NO and 1 NC  
 AC-15: 2 A at 415 Vac, 4 A at 240 Vac,  
 5 A at 110 Vac  
 DC-13: 0,25 A at 220 Vdc / 110 Vdc  
 Ui: 500 V, Uimp: 2,5 kV  
 Rated conditional short-circuit current: 1 kA  
 Fuse: RL6-25/6, 6 A, 500 Vac, 50 kA, Schneider

#### Product rating - NM8NDC-125B

Number of poles : 1P, 2P, 3P and 4P  
 Rated operational voltage (Ue) : 1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P, 250 Vdc for 1P  
 Rated ultimate short-circuit breaking capacity (Icu) : 25 kA at 1000 Vdc for 4P,  
 25 kA at 750 Vdc for 3P,  
 25 kA at 500 Vdc for 2P,  
 25 kA at 250 Vdc for 1P  
 Rated service short-circuit breaking capacity (Ics) : 25 kA at 1000 Vdc for 4P,  
 25 kA at 750 Vdc for 3P,  
 25 kA at 500 Vdc for 2P,  
 25 kA at 250 Vdc for 1P

#### Product rating - NM8NDC-125C

Number of poles : 1P, 2P, 3P and 4P  
 Rated operational voltage (Ue) : 1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P, 250 Vdc for 1P  
 Rated ultimate short-circuit breaking capacity (Icu) : 36 kA at 1000 Vdc for 4P,  
 36 kA at 750 Vdc for 3P,  
 36 kA at 500 Vdc for 2P,  
 36 kA at 250 Vdc for 1P  
 Rated service short-circuit breaking capacity (Ics) : 36 kA at 1000 Vdc for 4P,  
 36 kA at 750 Vdc for 3P,  
 36 kA at 500 Vdc for 2P,  
 36 kA at 250 Vdc for 1P

#### Product rating - NM8NDC-125S

Number of poles : 1P, 2P, 3P and 4P  
 Rated operational voltage (Ue) : 1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P, 250 Vdc for 1P  
 Rated ultimate short-circuit breaking capacity (Icu) : 50 kA at 1000 Vdc for 4P,  
 50 kA at 750 Vdc for 3P,  
 50 kA at 500 Vdc for 2P,  
 50 kA at 250 Vdc for 1P  
 Rated service short-circuit breaking capacity (Ics) : 50 kA at 1000 Vdc for 4P,  
 50 kA at 750 Vdc for 3P,  
 50 kA at 500 Vdc for 2P,  
 50 kA at 250 Vdc for 1P

#### Product rating - NM8NDC-125Q

Number of poles : 2P, 3P and 4P  
 Rated operational voltage (Ue) : 1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P  
 Rated ultimate short-circuit breaking capacity (Icu) : 70 kA at 1000 Vdc for 4P,  
 70 kA at 750 Vdc for 3P,  
 70 kA at 500 Vdc for 2P  
 Rated service short-circuit breaking capacity (Ics) : 70 kA at 1000 Vdc for 4P,  
 70 kA at 750 Vdc for 3P,  
 70 kA at 500 Vdc for 2P

### Product rating - NM8NDC-125H

Number of poles	:	2P, 3P and 4P
Rated operational voltage (Ue)	:	1000 Vdc for 4P, 750 Vdc for 3P, 500 Vdc for 2P
Rated ultimate short-circuit breaking capacity (Icu)	:	100 kA at 1000 Vdc for 4P, 100 kA at 750 Vdc for 3P, 100 kA at 500 Vac for 2P
Rated service short-circuit breaking capacity (Ics)	:	100 kA at 1000 Vdc for 4P, 100 kA at 750 Vdc for 3P, 100 kA at 500 Vac for 2P

### Additional information

#### NM8N DC – 125 C TM 125 4

a b c d e f g

a = model name: 'NM8N'

b = direct current: 'DC'

c = frame size: '125'

d = short-circuit capacity: 'B', 'C', 'S', 'Q' or 'H'

e = trip unit: 'TM' means thermal magnetic type

f = rated current: 16 A, 20 A, 25 A, 32 A, 40 A, 50 A, 63 A, 80 A, 100 A, 125 A

g = number of poles: '4' means 4P, '3' means 3P, '2' means 2P, '1' means 1P

Accessory type	Model
Auxiliary circuit	AX21-M8 / AL21-M8 (2P, 3P and 4P)
Shunt release	SHT21-M8 (2P, 3P and 4P)
Under-voltage release	UVT21-M8 (2P, 3P and 4P)
Electric operating mechanism	MOD21-M8 (3P and 4P)
Rotation handle	DRH21-M8 (3P and 4P)

End