



B1B





5

For 384V dc nominal 500V dc maximum rating the circuit breaker is suitable only for use with BPS. For ungrounded system only.

Wire 1 and 2	10-4 AWG (4-25 mm <sup>2</sup> )
	31 lb-in (3.5 N·m)

B1B





6

For 800V dc nominal 1000V dc maximum rating the circuit breaker is suitable only for use with BPS. For ungrounded system only.

Wire 1, 2 and 3	10-4 AWG (4-25 mm <sup>2</sup> )
Wire 3	more than 254mm(10 inches)
	31 lb-in (3.5 N·m)

B1B





7

Green  
OFF

Red  
ON

B1B



In order to protect the environment, when the product or its components are scrapped, please dispose of it as industrial waste or hand it over to the recycling station for disaggregation, recycling and reuse according to relevant national regulations.



Printed with environment-friendly paper

Copyright Noark. All Rights Reserved

na.noark-electric.com

11/2022

B1B




1

Battery Power Supply (BPS) Miniature Circuit Breaker

Installation Instructions  
Notice d'installation  
Instrucciones de montaje

NOARK

B1B




2

WARNING

DO NOT ATTEMPT TO INSTALL OR PERFORM MAINTENANCE ON EQUIPMENT WHILE IT IS ENERGIZED. DEATH, SEVERE PERSONAL INJURY, OR SUBSTANTIAL PROPERTY DAMAGE CAN RESULT FROM CONTACT WITH ENERGIZED EQUIPMENT. ALWAYS VERIFY THAT NO VOLTAGE IS PRESENT BEFORE PROCEEDING WITH THE TASK, AND ALWAYS FOLLOW GENERALLY ACCEPTED SAFETY PROCEDURES.

NOARK IS NOT LIABLE FOR THE MISAPPLICATION OR IMPROPER INSTALLATION OF ITS PRODUCTS

B1B




3

TH35-7.5

CLICK

B1B



4

CLICK